

# Environmentally Sensitive Lands Overlay (ESL) and Foothills Overlay (FO) Zoning Planning Plan Review

Grading and Drainage/Site Plan Requirements Zoning Ordinance Sec. 1.204; DS&PM 4-1.900			15.	Provide all wall/fence and retaining wall heights, both existing and proposed by elevation or footage. Heights shall include:
Site Plan Data				Top of Wall / Top of View Fence, Top of
1.		Provide the legal description, address, APN, QS, subdivision and lot number. If an address has not been assigned to the site by the City of Scottsdale, contact Records at (480) 312-2356 to obtain one.	16. 17.	Footing, and Top of Retaining Wall (when applicable, ex. cuts and fills).  Provide top of curb (if no curb, provide top of edge of road/pavement).  Call out the lowest finished floor elevation on
2.		Provide the current Zoning District on the site		the site plan using the 88 Datum. For remodels, the City of Scottsdale may have this
<ul><li>3.</li><li>4.</li><li>5.</li></ul>		plan. Provide associated case numbers on the right-hand plan margin. Provide the net lot area. Show the name, address and phone # of		information available at the Planning and Development Services Records Division located at 7447 E. Indian School Road, Suite 100; or by contacting the division at 480-312-2356. (SRC 37-25 and DS&PM 4-1.901.20)
6.		architect (or designer), engineer and owner on plan.  Note the landform classification (Lower Desert, Upper Desert, Hillside) in the site data.  (ZO Sec. 6.1091.A.1.J.)	18.	Comply with the development standards of the Zoning District and/or approved amended development standards and Section VII of the Zoning District as indicated on the City reviewed marked up site plan.
7.		Provide the CDS plan check number (this number is provided at the time the plans are logged into the city for review) along the right border or bottom right hand corner; a 1/4"	19.	Provide the following dimensions on the site plan:  a. Property dimensions;  (DS&PM 4-1.901.9.)
8.		minimum lettering shall be used on all sheets. Provide the amount of area enclosed by walls and building. The amount of area enclosed by walls and buildings shall not exceed the maximum areas indicated in ZO Sec. 6.1004.B.3.		<ul> <li>b.  The Zoning District's required setback;</li> <li>c.  The actual location of all proposed structures, including walls, on lot from the property lines;</li> </ul>
9.		Provide the total area under roof of all accessory buildings. The total area under roof of all accessory buildings shall not exceed the maximum areas indicated in ZO Sec. 6.1004.C.6.		<ul> <li>d.</li></ul>
10.		Provide the total area of each individual accessory building in square feet. Each accessory building area shall be provided separately and totaled. The total area of each individual accessory building shall not exceed the areas established in ZO Sec. 6.1004.C.7.		from the centerline to the property line; g. Identify existing and new easements, right-of-way, and improvements; (DS&PM 4-1.901.6.) h. Show water and sewer main size; water meter size and location.
Site	Plan I	Requirements .		The City of Scottsdale may have this information available at the Records
11. 12. 13. 14.		Size 24" x 36" G&D site plan. Show a vicinity map. Provide a north arrow on each site plan sheet. Include a written and graphic (bar) scale.		Department; or contact 480-312-2356.  i. Department; or contact 480-312-2356.  The additional dimensions indicated on the City reviewed marked up site plan.

Planning & Development Services



# Environmentally Sensitive Lands Overlay (ESL) and Foothills Overlay (FO) Zoning Planning Plan Review

20.		Show topography (existing and proposed) at a maximum of 2-foot intervals; include any proposed drainage facilities. (ZO Sec.			benefits easement on the adjacent property, if the footing or wall crosses the property line. (DS&PM 2-2.405)
		6.1091.A.1.g.)	29.		Identify on the site plan all boulders, boulder
21.	П	Show all existing & proposed utility main and	20.		features, boulder rolling, and rockfalls that
	_	service line locations to the structure & denote			meet the requirements as defined by Zoning
		utility type. (DS&PM 2-2.100)			Ordinance Definitions. (ZO Sec. 3.100, Sec.
22.	П	Site walls shall be setback a minimum of 5			6.1091.A.4.a., Sec. 6.1070.C.1.)
	_	feet from a CA, COS, HC, or OS line. (ZO	30.		Identify the above sea level height of all
		Sec. 1.204 and Sec. 6.1060; DS&PM 2-2)		_	protected peaks and ridges on the site or
23.		Retaining walls shall be set a minimum of 5			adjacent to the parcel within 400 feet. (Refer to
		feet, or one foot for each foot of the total depth			the City of Scottsdale's Protected Peaks and
		and height (bottom of footing to the top of the			Ridge maps, ZO Sec. 6.1070.D.)
		wall), which ever is greater from a CA, COS,	31.		All buildings shall be setback an average of
		HC, or OS line. Provide cross sections to			300 feet horizontally, and a minimum of 200
		verify techniques and demonstrate that the			feet horizontally from a protected peak or
		CA/COS/HC/OS is not being encroached			protected ridge. (ZO Sec. 6.1070.D.)
		upon by construction. (ZO Sec. 1.204 and	32.		If a septic system (tank and seepage field) is
	_	Sec. 6.1060; DS&PM 2-2)			used, show and call out the location on the
24.	Ш	Site walls shall not be constructed on the			site plan. The septic system shall not be
		property line without providing the City of			located in NAOS. (ZO Sec. 6.1100.B.1.)
		Scottsdale documentation from the adjacent			Reference the Maricopa County Septic
		property owner acknowledging that the site			Application and/or Permit Number. (DS&PM 7-
		wall will be constructed on the property line, if			1.300.A.)
		the footing or wall crosses the property line.	33.	Ш	Solid walls shall not be permitted within or
		a. If adjacent property owner			crossing a wash that has a water flow of 50 cfs
		authorization is not provided, add the			or greater. (SRC 47-72.7; and ZO Sec.
		following note to the Site Plan:	24		6.1070.G.1.l.)
		Construction of footing and worker	34.	Ш	All boulders, boulder features, boulder rolling,
		access shall not occur on adjacent property without express written			and rockfalls that meet the requirements as defined by Zoning Ordinance Definitions (ZO
		permission from the adjacent property			Sec. 3.100.) shall be preserved in place with a
		owner.			NAOS easement. Unless otherwise approved
25.		Site walls shall not exceed 6 feet in height on			by the Development Review Board, the NAOS
20.	ш	the property line in the required side and rear			easement shall include a 20 feet offset
		yards. (ZO Sec. 6.1004.B.1)			measured from the face of the boulders,
26.	П	Site walls shall not exceed 8 feet in height on			boulder features, boulder rolling, and rockfalls.
		the property line in the required side and rear			(ZO Sec. 6.1070.F)
		yards. (ZO Sec. 6.1004.B.3)	35.		Accessory building setbacks from the rear and
27.		A corral fence shall be set back 10 feet from a			side property line shall comply with ZO Sec.
		property line, trail easement, or pathway			6.1004.C.1.
	_	easement. (ZO Sec. 6.1004.B.4.C.)	36.		Accessory buildings shall be setback from an
28.	Ш	Retaining walls shall be set a minimum of 3			accessory building, main residence, and/or
		feet, or 1-foot for each foot of the total depth			guesthouse on an abutting lot in accordance
		and height (bottom of footing to the top of the			with ZO Sec. 6.1004.C.2.
		wall) from the property line unless applicant	37.	Ш	The minimum distance of an accessory
		provides to the City of Scottsdale			building and any other building on the same lot
		documentation of a recorded private use and			

**Planning & Development Services** 



# Environmentally Sensitive Lands Overlay (ESL) and Foothills Overlay (FO) Zoning Planning Plan Review

38. 39.		shall be provided in accordance with ZO Sec. 6.1004.C.3.  The minimum distance of an accessory building located within the portion of the property excluding the required front, side, and/or rear yards or between more than one main building on the same parcel shall be provided in accordance with ZO Sec. 6.1004.C.4.  No accessory building(s) may be closer to the front property line than the main building if the main building is at or with in the distance established in ZO Sec. 6.1004.C.5 of the property line.  Large buildings shall provide additional setbacks in accordance with ZO Sec. 6.1004.C.8.	48. 49. 50. 51.		revegetated NAOS for the length of the wall, for a width of 5 feet. (DS&PM 2-2.501.D.3) NAOS shall not be dedicated within 5 feet of a building. (DS&PM 2-2.501, Figure 2.2-9) NAOS dedicated w/in 10 feet of a building shall be considered revegetated NAOS for the length of the building (DS&PM 2-2.501, Figure 2.2-9). Undisturbed NAOS: 70% min; disturbed NAOS: 30% max. Revegetated NAOS applied at 100% credit. (ZO Sec. 6.1060.D.) If a pool is to be constructed, and the only access to the pool location is through a designated NAOS area, a width of 10 feet (or a portion of the NAOS that would provide a 10 foot access width) for the length of the affected NAOS shall be considered revegetated NAOS (DS&PM 2-2.405.C.1).
NAO:	S Rec	<u>quirements</u>	Cute	and	Fille
41.		If a lot's NAOS requirement is not predetermined during the platting or land	<u>Cuts</u> 52.	and ∣	Fills  Cuts and fills over 6 to 8 feet may require a
		division process, provide the slope data calculations and table in accordance with Section 6.1060.A.2.1 Table A of the Zoning Ordinance.	53.		separate review and approval. Prior to resubmittal, submit a pre-application meeting request to the One Stop Shop. Cuts and fills exceeding 8 feet require a Staff
42.		Provide the square footage of <u>required</u> and <u>provided</u> NAOS including the <u>undisturbed</u> and <u>disturbed</u> percentages. <b>Calculations must be</b>	JJ.		Approval or the DRB approval as determined by Current Planning staff. Provide evidence of this approval with the case # on the plans.
43.		provided. (ZO Sec. 6.1060.D.) Show proposed and existing NAOS location(s) on the site plan (ZO Sec. 6.1060.A.6.)	54.		Plans will not be accepted for review until these approvals have been obtained.  Provide cross sections through the site and
44.		Show all utility locations and service connections to the structure on the site plan. (water, sewer, septic and all dry utilities) If the	01.		building as indicated on the City reviewed marked up site plan.
		connections encroach into NAOS, 5' of	Site	Plan I	<u>Notes</u>
		revegatation is to be shown on each side of	55.		Pools require separate approval and permit.
45.		utility line and accounted for in the data table. (ZO Sec. 6.1070.A.4.) NAOS shall be located in "high priority" areas.	56.		Pools shall not be emptied or backwashed into washes, streets, NAOS, scenic corridors, on to
40.		(washes, continuity w/ adjacent properties' NAOS, preservation of most significant natural	57.		an adjacent lot, or tract of land. (ZO Sec. 6.1100.B.1.; and DS&PM 2-2.501.D.4.c.) All mechanical equipment (air conditioner,
46.		features) (ZO Sec. 6.1060.F.3.)  NAOS must be a min. 30 feet in width (20 feet adjacent to roadways) and have a minimum of 4000 sq. ft. contiguous area. (ZO Sec.			pool equip. etc.) shall be screened a minimum of 1 foot above the highest portion of the equipment from all sides and shall be compatible with the adjacent building. Show
47.		6.1060.F.1.a-b.) NAOS areas dedicated adjacent to site and retaining walls shall be considered			location of equipment on site plan.

**Planning & Development Services** 



# Environmentally Sensitive Lands Overlay (ESL) and Foothills Overlay (FO) Zoning Planning Plan Review

58.	A guesthouse shall never be offered for rent. (ZO Sec. 5.012.A.6.c. and Sec. 5.102.A.6.c.)	68.		Any proposed modifications to natural watercourses and all walls and fences
59.	A guesthouse shall not exceed a gross footprint size greater than 50% of the foot print size of the principal building. (ZO Sec. 5.012.A.6.b.)			crossing natural watercourses shall be designed in accordance with the standards and policies specified in chapter 37 (drainage and floodplain ordinance) of the Scottsdale
60.	Exterior materials and paint colors shall not exceed a value and/or chroma of 6 as indicated in the Munsel Book of Color on file in the City of Scottsdale's Planning & Development Department. The City may require color samples to verify compliance.	69.		Revised Code. (ZO Sec. 6.1070.G.1.l.) Land designated as NAOS shall be permanently maintained as open space. The property owner shall maintain all designated NAOS. (ZO Sec. 6.1060.A.3-4 and Sec. 6.1100.B.1.)
61.	(ZO Sec. 6.1070.G.1.h.)  Materials used for exterior surfaces of all structures shall blend in color, hue, and tone with the surrounding natural desert setting to avoid high contrast. (ZO Sec. 6.1070.G.1.c.)	70.		All exterior lighting below 3 feet in height shall be fully shielded. All exterior lighting above 3 feet in height shall consist of horizontal full-cutoff fixtures and directed downward, except lights utilized for security purposes.
62.	Surface materials of walls, retaining walls or fences shall be similar to and compatible with those of the adjacent main buildings.  (ZO Sec.6.1070.G.1.d.)	71.		(ZO Sec. 6.1070.G.1.f and Sec. 6.1004.D.1.) All exterior lights including those mounted to buildings/structures and on poles shall not exceed a height of sixteen (16) feet. (ZO Sec.
63.	Plant materials not indigenous to the ESL area shall be limited to enclosed yard areas and non-indigenous plants that have the potential of exceeding twenty (20) feet in height are prohibited. Turf shall be limited to enclosed areas not visible from a lower elevation.	72.		6.1004.D.2.). Exemption: Lights that are connected to a delay switch that do not stay on more than 15 minutes for security purposes shall not be required to be shielded or contain horizontal cutoffs. (ZO Sec. 6.1004.D.3.) Exterior lighting should be low scale and
64.	(ZO Sec.6.1070.G.1.i-j.) Reflective building materials are prohibited. (DS&PM 2-2.501.A.2.)			directed downward, recessed or shielded so that the light source is not visible from residential developments in the area or from a
65.	Reflective building and roofing materials (other than windows and solar panels) including materials with high gloss finishes and bright, untarnished copper, aluminum, galvanized steel or other metallic surfaces, shall be textured or have a matte or non-reflective			public viewpoint. Exterior fixtures shall not generally exceed a height of 6 feet measured from the nearest adjacent grade to the top of the fixture (lower heights may be required by the Inspection or Code Enforcement staff). (ZO Sec. 6.1070.G.1.f.)
	surface treatment to reduce the reflections of sunlight onto other property. (ZO Sec. 6.1070.G.1.b.)	73.		Where on-site walls are placed adjacent to NAOS areas at least 50 percent of the wall surface shall be a view fence.
66.	Mirrored surfaces or any treatments that change ordinary glass into a mirrored surface are prohibited. (ZO Sec. 6.1070.G.1.a.)	74.		(DS&PM 2-2.501.B.2.b.) Temporary/Security Fencing that is required or is optionally provided shall be in accordance
67.	The owner shall incorporate development design and construction techniques that blend in scale, form and visual character to minimize exposed scars to the satisfaction of the			with the Zoning Ordinance and the Design Standards and Policies Manual. (ZO Sec. 7.700 and Sec. 6.1071.A.6, and DS&PM 1- 1.407)
	Planning & Development Department. (ZO Sec. 6.1070.G.1.e.)	75.	Ш	In accordance with the Zoning Ordinance, a registered surveyor shall stake and rope the

**Planning & Development Services** 



# Environmentally Sensitive Lands Overlay (ESL) and Foothills Overlay (FO) Zoning Planning Plan Review

		most restrictive area defined by the	Rec	uire	d Dedication Documents
76.		construction envelope and NAOS easement as shown on the site plan. (ZO Sec. 6.1070.A.5)  No paint color or surface treatment shall be used which has a Light Reflective Value (LRV) greater than 35%.(ZO Sec.6.1070.G.1.g.&k)	84.		Provide the originally signed City of Scottsdale Policy on Appeals of Dedications, Exactions, or Zoning Regulations form. This form is to be signed by the property owner, and may be obtained from the City's website at: <a href="http://www.scottsdaleaz.gov/Assets/Public+W">http://www.scottsdaleaz.gov/Assets/Public+W</a>
Acco over shal	ordan lay (E	s that are exempt from the ESL Areas in the ce with the 2004 Amendment to the ESL EXE EXEMPTIONS Schedule Sec. 6.1022.B.) ace # 75 and # 76 with # 77 and # 78 ely.  A registered surveyor shall stake and rope or	85.		ebsite/bldgresources/Appeals+of+Dedication\$! 2c+Exactions+or+Zoning+Regulations.pdf. Provide a Commitment for Title Insurance that includes a complete Schedule A and B. The City's requirements for an acceptable Commitment for Title Insurance may be obtained from the City's website at:
78.		fence the NAOS easement in accordance with the site plan and the easement legal description.  No paint colors shall be used which have a Light Reflective Value (LRV) greater than 40%.	86.		http://www.scottsdaleaz.gov/bldgresources/PlanReview/title.asp. Provide the original 8-½" x 11" legal description and exhibit, sealed by a registered professional. (Forms that contain fax information will not be accepted)
acco	ordano	Il Requirements for ESL Areas in ce with the 2004 Amendment to the ESL ZO Sec. 6.1022.B.)			<ul> <li>a.  Natural Area Open Space</li> <li>b.  Scenic Corridor Easement</li> <li>c.  Public Non-Motorized Access</li> <li>Easement</li> </ul>
79.		Site walls must be setback 15 feet from side and rear property lines. This applies only to residential parcels containing an area of 35,000 sq ft or larger. (ZO Sec.6.1071.A.4.)			d. Right-of-Way e. Drainage Easement f. Public Utility Easement g. Vehicular Non-Access Easement
80.	Washes of 50 cfs or greater flow shall be identified and watercourse(s) shall be unaltered. If watercourse(s) are altered, provide a copy of the wash modification approval letter and reference the case number on the site plan. (ZO Sec. 6.1070.G.1.l. and	h Other Provide the original Easement dedication form(s) to be signed and notarized by owner(s). (Forms that contain fax information will not be accepted). See Maricopa County form requirements: http://recorder.maricopa.gov/web/formreq.aspx.			
81.		6.1091.A.4.b.) Applications that have received a hardship exemption shall provide the case number on the site plan. (ZO Sec. 6.1022.D)	88.		Provide the original Confirmation of New Dedication form(s) signed and notarized by all beneficiaries listed in Schedule B of the Title
82.		Site walls shall not be provided in NAOS areas or disrupt the continuity of NAOS corridors. (ZO Sec. 6.1071.A.2.a.)			Insurance Commitment, if there are any liens or loans on the property. (Forms that contain fax information will not be accepted). See
83.		Identify the specific location of the construction envelope on site plan. The construction envelope consists of an area enclosed by a line extending 15 feet out from all disturbances on lot. (ZO Sec. 6.1071.A.6. and Sec. 6.1070.A.3, Figure 6.1070.B)			Maricopa County form requirements: <a href="http://recorder.maricopa.gov/web/formreq.aspx">http://recorder.maricopa.gov/web/formreq.aspx</a> .

**Planning & Development Services** 



# Environmentally Sensitive Lands Overlay (ESL) and Foothills Overlay (FO) Zoning Planning Plan Review

Architectural Elevations  89. Native plant inventory show the nursery site I materials are to be sto (ZO Sec. 7.504.C.)	location where plant pred during construction.
materials are to be sto	ored during construction.
Floor88 (LFF88 or LF88) and/or elevations of the roof parapet, top of the roof tile, and chimneys. (ZO Sec. 1.204., DS&PM 4- Contractor shall perform	oroved salvage m the native plant
90. Measured from natural (pre-disturbed) grade, salvage contractors is	az.gov/Assets/Public+W
91. Measured from natural (pre-disturbed) grade, the maximum building height shall not exceed feet in accordance with the ESL.  Exemptions Schedule – Specific Development  Madditions and modification indicate all native plant improvement and the control of the area of improvement in the are	ation shall inventory and its within 50 feet of the construction access to
peak or ridge. (ZO Sec. 6.1070.D)  due to construction and associated with this ap	on, add the following Drainage Site Plan: ermitted to be disturbed and related activities
Roof Height Analysis Plan ZO Sec. 1.204  Povegetation Plans	
93. Provide a roof height analysis plan to demonstrate compliance with Zoning Ordinance Section 6.1070.B.1.b or 6.1022.B.  94. The roof height plan shall include all natural topography at a maximum of 1 foot intervals.	revegetation plan. A equired when evegetation areas, slope on, and any area that
Native Plant Requirements Revegetation Plan Data	
Native Plant Inventory & Salvage Plan  Native Plant Inventory & Salvage Plan  104. Show the project name 105. Show a vicinity map or 106. Provide the zoning on	n the cover.
97. Comply with the Scottsdale Native Plant Ordinance. (SRC Chapter 46, Article V; and ZO Sec. 7.500.).	dress on the cover.
98. Native plant inventory & salvage plan shall show locations of all protected species on a 24" x 36" Native Plant Inventory & Salvage Plan or on the Grading & Drainage Site Plan.	and owner. n each sheet.
(Separate 8 ½" x 11" native plant inventory 111. Provide a written and gassessments will not be accepted.).	graphic (bar) scale on

Planning & Development Services



# Environmentally Sensitive Lands Overlay (ESL) and Foothills Overlay (FO) Zoning Planning Plan Review

112.		Provide Blue Stake note and phone number	126.		All right-of-way improvements (streets,
113.		when multiple plan sheets are used, a plan key shall be provided on the cover and the corresponding sheets.	127. 128.		sidewalks, trails, etc.) adjacent to the project shall be shown and dimensioned.  Show the location of all plants to be installed.  Provide a typical 20' x 20' revegetation
114.		Associated CDS plan check number (this number is provided at the time the plans are logged into the city for review) along the right border or bottom right hand corner; a 1/4"	120.		sample. This may be only utilized for revegetation areas 10 feet and less in width. Plant symbols shall be provided. The designer may chose to show the plant material in areas
115.		minimum lettering shall be used on all sheets. The revegetation plans shall be drawn at the same scale as the grading and drainage /site plans or larger.	129.		less than 10 feet and not provided the sample. Provide the sight distance triangles (SDT) and or/ Traffic Safety Triangle (TST) drawn in accordance to the Design Standards and Policy Manual, shall be shown to the curb line.
Reve	getat	tion Plan Requirements			(ZO Sec. 7.104; DS&PM 2-1.1001, Figures
116.		Any berming or grading of 1 foot or greater must be shown on the grading and drainage plan.			5.3-26 (driveway and intersection) and 5.3-27 (corners)): www.scottsdaleaz.gov/design/DSPM.
117.		The revegetation plans shall contain an overall plant palette.	130.		Plants in SDT and/or TST shall not exceed a maximum growth height of 2 feet, with the
118.		Each plant type shall be identified by its common and botanical name.			exception of trees. Single trunk trees may be placed in an SDT and/or TST as long as their canopies are maintained above 7 feet in
119.		Each plant type shall have its own individual symbol. When the same plant is utilized in multiple sizes, each size shall be identified	131.		height upon installation, as measured above the nearest street elevation.  Hydro-seed areas shall be clearly identified on
120.		separately.  All plants shall be assigned a planting size; trees shall be identified by the caliber inch size.			the plans. Hydro-seed mixtures shall not be utilized as a major revegetation method, but as supplement to the maximum spacing
121.		All salvage plant material, deemed to be salvageable and to be relocated shall be identified by their common and botanical	132.		between plants. ESL areas surface treatment shall be replaced by raked native soils. Desert pavement (topsoil salvage) is encouraged. Decomposed
122.		names. Hydro-seed/hydro-mulch-seed mixtures shall be identified separately from the plant list.		_	Granite is prohibited in NAOS, and where visible off site.
		Each plant in the hydro-seed/hydro-mulch-seed mixture shall be identified by its common and botanical name.	133.		Identify methods utilized to preserve natural area open space in designated environmentally sensitive lands (see notes
123.		The hydro-seed/hydro-mulch-seed mixtures schedule shall be include the pounds of seed/mulch-seed per 1000 sq ft.	134.		All plants utilized to revegetated NAOS, and unenclosed areas to be landscaped shall
124.		Identify the location of the construction envelope. (The construction envelope shall be shown as required by the ZO ESL Exemption Schedule 6.1022, Figure 6.1070.B, Sec. 6.1071.A.6., and Sec. 6.1070.A.3.)			comply with the Environmental Sensitive Lands Ordinance. All areas that are not enclosed shall utilize plants from the City of Scottsdale's Indigenous Plants for Environmentally Sensitive Lands Plant List.
125.		All easements shall be shown and labeled, including NAOS			ESL Plant list may be obtained from the City's Website at:

**Planning & Development Services** 



# Environmentally Sensitive Lands Overlay (ESL) and Foothills Overlay (FO) Zoning Planning Plan Review

		http://www.scottsdaleaz.gov/codes/nativeplant/eslo.asp.	144.		Non-native decomposed granite shall not be provided in NAOS area or unenclosed areas.
135.		All plants utilized in the right-of-way shall be listed in the Arizona Department of Water	145.		Areas within the SDT are to be clear of landscaping, signs, or other visibility
		Resource's (ADWR) and the ESL plant lists.			obstructions with a height greater than 2 feet.
136.		Any disturbance to a Scenic Corridor shall be			Trees within the safety triangles shall have a
		revegetated in accordance with the City of			canopy that begins at 7 feet in height upon
		Scottsdale's Scenic Corridors Design			installation. All heights are measured from
		Guidelines. The Scenic Corridors Design		_	nearest street line elevation.
		Guidelines may be obtained from the City's	146.	Ш	Retention/detention basins shall be
		website at:			constructed solely from the approved civil
		http://www.scottsdaleaz.gov/planning/corridorp			plans. Any alteration of the approved design
137.	$\Box$	lans/intro. Revegetated NAOS areas shall utilize plant			(additional fill, boulders, etc.) shall require additional final plans staff review and approval.
137.	Ш	species and density similar to the adjacent	147.		All rights-of-way adjacent to this property shall
		undisturbed areas. It is preferred that	177.	Ч	be revegetated and maintained by the
		salvaged plant material is utilized in			property owner.
		revegetated NAOS Areas.	148.		No landscape lighting is allowed in the NAOS
138.		Revegetation in detention basins and			areas.
	_	channels should comply with DS&PM 2-1.903.	149.		All signs require separate permits and
139.		New landscaping shall be located so that there			approvals.
		are no conflicts with public utilities. Trees and	150.	Ш	New landscaping, including salvaged plant
		saguaros shall not be planted in the Public			material, and landscaping indicated to remain,
		Utility Easements(s) or within 7 feet of a public water line and/or public sewer line. (DS&PM 2-			which is destroyed, damaged, or expires during construction shall be replaced with like
		1.1001).			size, kind, and quantity prior to the issuance of
140.		Revegetation plans are not permitted to			the Certificate of Occupancy / Letter of
	_	include construction details for pools, retaining			Acceptance to the satisfaction of the
		walls, walls or fences over three feet, and			Inspection Services Staff.
		fireplaces. Any construction details pertaining	151.		All revegetated NAOS shall be watered for 3
		to these items must be removed prior to			years. At the end of 3 years or once plant
		approval. These details shall be included on			material has become established, the irrigation
		the site plan, except pools and fire places.			systems to the revegetated NAOS shall be
		Pools and fire places require separate	450		permanently disconnected.
		application review approval and permit.	152.	Ш	All landscape irrigation systems shall be separated from the domestic water supply by
Rove	nota	tion Plan Notes			a backflow preventor in accordance with the
					City of Scottsdale MAG Supplement
141.		Minor modification to the approved			Standards Detail number 2354.
		revegetation plan may be approved as	153.		No irrigation shall be provided to undisturbed
142.		required by the Inspection Services staff.  All salvage plant relocation and revegetation		_	Natural Area Open Space (NAOS) areas.
142.	Ш	shall be completed prior to the issuance of the	154.	Ш	Plants that are not indigenous to the ESL area
		Certificate of Occupancy.			shall be limited to enclosed yard areas, and
143.		Boulders and salvaged surface material shall			non-indigenous trees shall only be located in
		be provided in a disturbed area to match and			the rear yards, plant material that have the potential of exceeding twenty (20) feet in
		blend with surrounding desert character. (ZO			height is prohibited. Turf shall be limited to
		Sec. 6.1060.)			noight is profilotiod. Tall stall be littlited to

**Planning & Development Services** 



Environmentally Sensitive Lands Overlay (ESL) and Foothills Overlay (FO) Zoning Planning Plan Review

155.		enclosed areas not visible from a lower elevation. (ZO Sec.6.1070.G.1.i-j.) A registered surveyor shall stake and rope the construction envelope and NAOS easement in accordance with the site plan. The construction envelope and NAOS area staked is the must be the most restrictive in accordance with the Zoning Ordinance.
Acco overl www	rdan ay (E .scot	ons that are exempt from the ESL Areas in ce with the 2004 Amendment to the ESL xemption schedule at tsdaleaz.gov/codes/ESLO) shall replace # 156 respectively.
156.		A registered surveyor shall stake and rope the NAOS easement in accordance with the site plan and the easement legal description.
ZO S	ec. 6.	<u>Lighting Review</u> 1000., Sec. 6.1010., Sec. 7.600.; and hapter 2-1.
157.		Provide 3 copies of the exterior lighting manufacture cut sheets on a 24" x 36" minimum paper size. Each exterior light cut sheet provided shall be legible. The cut sheet or plans shall clearly identify the light fixture manufacture number utilized, wattage, style, and lamp type. (State law prohibits Mercury Vapor lighting.) Please refer to the: <a href="http://www.scottsdaleaz.gov/codes/Zoning/Interp/_docs/VisibilityExteriorLightingESL.pdf">http://www.scottsdaleaz.gov/codes/Zoning/Interp/_docs/VisibilityExteriorLightingESL.pdf</a>
158.		Provide the electrical floor plan and/or site plan and indicate the location all exterior light fixtures.